



PROJECT	TYPE
CATALOG NUMBER	

KEY FEATURES

- 120V
- 3-3/8" trim diameter (round), 3-1/8" x 3-1/8" (square)
- 2-1/2" recess depth
- Dimmable
- Up to 550 lumens
- 90+ CRI
- IC rated (ceiling clearance required: 2-1/2" for Romex, 3-1/2" for MC or BX installations)
- No visible glare
- Die-cast construction
- Quick and easy installation
- In-line junction box connected by 12" TwistLock cable
- Snap-in spring clips installation

PRODUCT DESCRIPTION

Excellent color rendition and high lumens in a recessed, 3" deep pregressed, IC rated, damp location, round and square trim downlight that features an inline junction box connected by a modular twist-connector. Perfect for any application where glare free illumination is desirable. Available in 2700K or 3000K color temp and white semi-gloss finish. Extenders available. See below.



ELECTRICAL

- 8W
- Rated life: 50,000 hrs.

OPTICS

- 2700K, 3000K

CERTIFICATION

- ETL
- Title 24
- Energy Star

WARRANTY

- 5 year warranty

ORDERING INFORMATION

Catalog No.	Trim	Recess Depth	Trim Dimensions	Wattage	Lumens	CRI	Color Temp.*
MDL-3R-27-WH	Round	2-1/2"	3-3/8" Dia.	8W	545	90+	2700K
MDL-3R-30-WH	Round	2-1/2"	3-3/8" Dia.	8W	550	90+	3000K
MDL-3S-27-WH	Square	2-1/2"	3-1/8" Sq.	8W	545	90+	2700K
MDL-3S-30-WH	Square	2-1/2"	3-1/8" Sq.	8W	550	90+	3000K

* Kelvin temperature (color) ±100K

ACCESSORIES

Catalog Number	Description
RSD-5FT-EXT	5' extension cord for MDL Series downlights
RSD-10FT-EXT	10' extension cord for MDL Series downlights
RSD-20FT-EXT	20' extension cord for MDL Series downlights
MDL-NCP	Universal mounting plate for new construction

