



PROJECT	TYPE
CATALOG NUMBER	

PRODUCT DESCRIPTION

Excellent color rendition and high lumens in a 3" mini-adjustable, IC rated, damp location, round trim downlight that features an inline junction box connected by a modular twist-connector. 360° rotation, 30° tilt on axis for precise beam control. Perfect for wall wash or focus aiming applications. Available in 2700K or 3000K color temp and white semi-gloss finish. Flexible modular extended connectors available. Extenders available. See below.

KEY FEATURES

- 120V
- 3-3/8" trim diameter, 1-1/2" recess depth
- Dimmable
- Up to 550 lumens
- 90+ CRI
- IC rated (ceiling clearance required: 2-1/2" for Romex, 3-1/2" for MC or BX installations)
- Adjustable gimbal (360° rotation - 30° tilt on axis)
- Die-cast construction
- Quick and easy installation
- In-line junction box connected by 12" TwistLock cable
- Snap-in spring clips installation

ELECTRICAL

- 8W
- Rated life: 50,000 hrs.

OPTICS

- 2700K, 3000K
- 30° beam angle

CERTIFICATION

- ETL
- Title 24
- Energy Star

WARRANTY

- 5 year warranty



ORDERING INFORMATION

Catalog No.	Recess Depth	Trim Diameter	Wattage	Lumens	CRI	Color Temp.*
MDL-3AR-27-WH	1-1/2"	3-3/8"	8W	545	90	2700K
MDL-3AR-30-WH	1-1/2"	3-3/8"	8W	550	90	3000K

ACCESSORIES

* Kelvin temperature (color) ±100K

Catalog Number	Description
RSD-5FT-EXT	5' extension cord for MDL Series downlights
RSD-10FT-EXT	10' extension cord for MDL Series downlights
RSD-20FT-EXT	20' extension cord for MDL Series downlights
MDL-NCP	Universal mounting plate for new construction

