



PRODUCT DESCRIPTION

A 9-1/2" diameter circular surface mount downlight. Constructed of a high quality die-cast aluminum body with translucent white polycarbonate diffuser lens for low glare. This Title 24 approved, wet location fixture maintains uniform intensity of up to 1850 lumens. Mounts to standard 4" outlet box.

120VAC SURFACE MOUNT WET LOCATION TITLE 24 COMPLIANT DOWNLIGHT

FEATURES

- 120VAC operation
- 22W
- 2700K / 3000K
- 90+ CRI
- Die-cast aluminum body with translucent white polycarbonate diffuser
- Up to 1850 lumens
- Dimmable
- Surface mounts to standard 4" outlet box or an existing 8" pot light.

ELECTRICAL

- Remote power supply not required

LABEL

- Title 24
- ETL
- IP67 for wet location
- Energy Star

APPLICATIONS

- Hallway lighting
- Commercial and institutional downlighting
- Hospitality corridor lighting

WARRANTY

- 5 year warranty

PRODUCT ORDERING INFORMATION

Catalog No.	Dimensions	Wattage	Lumens	Color Temp.*	CRI	Finish
S9-2790-WH	9-1/2" dia. x 1-3/8" depth	22W	1800	2700K	90+	White
S9-3090-WH	9-1/2" dia. x 1-3/8" depth	22W	1850	3000K	90+	White
S9-4090-WH	9-1/2" dia. x 1-3/8" depth	22W	1900	4000K	90+	White

* Kelvin temperature (color) ± 200K

