

PRODUCT OVERVIEW

Able to achieve color temps. of 2700K, 3000K and 4000K in a single fixture, this dimmable, tunable white undercabinet fixture features excellent color rendering in a powder coated aluminum housing with polycarbonate lens. Low profile and easy to mount in 8”, 16”, 24” and 32” lengths.

KEY FEATURES

- Tunable white - 2700K, 3000K, 4000K
- Damp location
- Powder coat aluminum housing
- Low profile (under one inch)
- Dimmable (Triac)
- Screwdriver slot for easy open
- Durable polycarbonate lens with even light distribution
- Modular - easy to connect multiple fixtures for longer runs
- Wago® wire connectors
- Captive screws for easy and quick installation

ELECTRICAL

- 120V (remote power supply not required)
- Color temps accessed through temperature slide switch
- Rated life: 50,000 hrs.

OPTICS

- 90+ CRI
- 2700K, 3000K, 4000K

CERTIFICATION

- ETL, Title 24, Energy Star, JA8

WARRANTY

- 5 year warranty



TOP: On/Off Switch
BOTTOM: 3-Position Color Temp. Switch



PRODUCT ORDERING

Catalog Number	Length	Wattage	Lumens	CRI	Finish
UCTUN-8-WH	8" / 203mm	6W/bar	400/bar	90+	White
UCTUN-8-BZ	8" / 203mm	6W/bar	400/bar	90+	Bronze
UCTUN-16-WH	16" / 406mm	10W/bar	850/bar	90+	White
UCTUN-16-BZ	16" / 406mm	10W/bar	850/bar	90+	Bronze
UCTUN-24-WH	24" / 610mm	14W/bar	1000/bar	90+	White
UCTUN-24-BZ	24" / 610mm	14W/bar	1000/bar	90+	Bronze
UCTUN-32-WH	32" / 1100mm	16W/bar	1150/bar	90+	White
UCTUN-32-BZ	32" / 1100mm	16W/bar	1150/bar	90+	Bronze

Each fixture includes one (1) conduit fitting and (1) UCTUN-EZ-1 connector.



ACCESSORIES

Catalog Number	Description
UCTUN-CP6-WH	Plug-in 5' power cord - white
UCTUN-EZ-1	Fixture to fixture connector - white
UCTUN-EZ-6	6" Flexible fixture to fixture connector - white
UCTUN-EZ-12	12" Flexible fixture to fixture connector - white
UCTUN-QB	Quick-Box wiring junction box with EZ connectors and knock-outs

PRODUCT DIAGRAM

