



8165 E Kaiser Blvd. Anaheim, CA 92808
 p. 714.282.2270
 f. 714.676.5558

Report No: L041609102

Date: 5/2/2016



NVLAP LAB CODE 200927-0

Report No: L041609102

Report Prepared For: GM LIGHTING
 9830 W 190th St, Torrance, CA 90503

Model Number: LTR300-30

Test: Electrical and Photometric tests

Standards Used: Appropriate part or all test guidelines were used for test performed:
IESNA LM79: 2008 Approved Methods for Electrical and Photometric Measurements of Solid-State Lighting Products
ANSI NEMA ANSLG C78.377: 2008 Specification of the Chromaticity of Solid State Lighting Products
ANSI C82.77:2002: Harmonic Emission Limits-Related Quality Requirements for Lighting Equipment

Description of Sample: Client submitted the sample. Catalog number is LTR300-30. Received in working and undamaged condition. No modifications were necessary.

Testing Condition: Fixture is tested with no special conditions.

Sample Arrival Date: 4/28/16

Date of Tests: 4/29/16 - 5/2/16

Seasoning of Sample: No seasoning was performed in accordance with IESNA LM-79.

Equipment List

Equipment Used	Model No	Stock No	Calibration Due Date
Chroma Programmable AC Source	61604	PS-AC02	--
Yokogawa Digital Power Meter	WT210	MT-EL06-S1	11/18/16
Xitron Power Analyzer	2503AH	MT-EL01	11/30/16
ITECH DC Power Supply	IT6122	PSDC-03-S1	11/17/16
Fluke Digital Thermometer	52k/J	MT-TP02-GC	11/24/16
LLI Type C Goniophotometer System	RMG-C-MKII	CD-LL04-GC	--
LLI 2M Sphere	2MR97	CD-SN03-S2	--
LLI Spectroradiometer	SPR-3000	MT-SC01-S2	Before Use

*All Results in accordance to IESNA LM-79-2008: Approved Method for the Electrical and Photometric Testing of Solid-State Lighting.

Test Summary

Manufacturer:	GM LIGHTING
Model Number:	LTR300-30
Driver Model Number:	N/A
Total Lumens:	735.13
Input Voltage (VDC):	12.00
Input Current (Amp):	0.71
Input Power (W):	8.61
Input Power Factor:	1.00
Current ATHD @ 120V(%):	N/A
Current ATHD @ 277V(%):	N/A
Efficacy:	85
Color Rendering Index (CRI):	82
Correlated Color Temperature (K):	3014
Chromaticity Coordinate x:	0.4404
Chromaticity Coordinate y:	0.4129
Ambient Temperature (°C):	25.0
Stabilization Time (Hours):	1:05
Total Operating Time (Hours):	1:25
Off State Power(W):	0.00





FIG. 1 LUMINAIRE

*All Results in accordance to IESNA LM-79-2008: Approved Method for the Electrical and Photometric Testing of Solid-State Lighting.




Wavelength	W/m ² nm	440	0.0011	510	0.0038	580	0.0090	650	0.0066	720	0.0011
380	0.0000	450	0.0037	520	0.0045	590	0.0096	660	0.0055	730	0.0008
390	0.0000	460	0.0046	530	0.0052	600	0.0099	670	0.0044	740	0.0006
400	0.0000	470	0.0033	540	0.0059	610	0.0098	680	0.0035	750	0.0005
410	0.0000	480	0.0024	550	0.0066	620	0.0093	690	0.0027	760	0.0003
420	0.0001	490	0.0024	560	0.0075	630	0.0086	700	0.0020	770	0.0002
430	0.0004	500	0.0030	570	0.0083	640	0.0076	710	0.0015	780	0.0002

CRI & CCT

x	0.4404
y	0.4129
u'	0.2490
v'	0.5253
CRI	82.10
CCT	3014
Duv	0.00300

R Values

R1	79.91
R2	90.33
R3	97.22
R4	77.77
R5	78.80
R6	86.90
R7	84.48
R8	61.51
R9	12.78
R10	77.00
R11	74.70
R12	63.52
R13	82.17
R14	98.75



*All Results in accordance to IESNA LM-79-2008: Approved Method for the Electrical and Photometric Testing of Solid-State Lighting.

Test Methods

Photometric Measurements - Goniophotometer

A Custom Light Laboratory Type C Rotating Mirror Goniophotometer was used to measure candelas(intensity) at each angle of distribution as defined by IESNA for the appropriate fixture type.

Ambient temperature is set to 25°C and is measured from the center of the fixture, within 1ft from the outside of the fixture. Temperature is maintained at 25°C throughout the testing process and the sample is stabilized for at least 30mins and longer as necessary for the sample to achieve stabilization.

Electrical measurements are measured using the listed equipment.

Spectral Measurements - Integrating Sphere

A Sensing Spectroradiometer SPR-3000, in conjunction with Light Laboratory 2 meter integrating sphere was used to measure chromaticity coordinates, correlated color temperature(CCT) and the color rendering index(CRI) for each sample.

Ambient temperature is set to 25°C and is measured from the center of the fixture, within 1ft from the outside of the fixture. Temperature is maintained at 25°C throughout the testing process and the sample is stabilized for at least 30mins and longer as necessary for the sample to achieve stabilization.

Electrical measurements are measured using the listed equipment.

Disclaimers:

This report must not be used by the customer to claim product certification, approval or endorsement by NVLAP, NIST or any agency of Federal Government.

Report Prepared by : Keyur Patel

Test Report Released by:



Jeff Ahn
Engineering Manager

Test Report Reviewed by:



Steve Kang
Quality Assurance

**Attached are photometric data reports. Total number of pages: 9*



8165 E. Kaiser Blvd. Anaheim, CA 92808
 p. 714.282.2270
 f. 714.676.5558

Photometric Test Report

IES INDOOR REPORT
PHOTOMETRIC FILENAME : L041609102.IES

DESCRIPTION INFORMATION (From Photometric File)

IESNA:LM-63-2002
 [TEST] L041609102
 [TESTLAB] LIGHT LABORATORY, INC.
 [ISSUEDATE] 5/2/2016
 [MANUFAC] GM LIGHTING
 [LUMCAT] LTR300-30
 [LUMINAIRE] 4 FT HO Flexible LED Linear Ribbon
 [LAMPPOSITION] 0,0
 [LAMPCAT] N/A
 [OTHER] INDICATING THE CANDELA VALUES ARE ABSOLUTE AND
 [MORE] SHOULD NOT BE FACTORED FOR DIFFERENT LAMP RATINGS.
 [POWER SUPPLY] 12VDC CONSTANT VOLTAGE SOURCE
 [INPUT] 12VDC, 8.61W
 [TEST PROCEDURE] IESNA:LM-79-08

CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	735
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	85
Total Luminaire Watts	8.61
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.28
Spacing Criterion (90-270)	1.28
Spacing Criterion (Diagonal)	1.40
Basic Luminous Shape	Rectangular
Luminous Length (0-180)	0.01 ft
Luminous Width (90-270)	4.00 ft
Luminous Height	0.00 ft

LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	65205	65525	65745
55	63197	63591	64102
65	59034	59435	59778
75	50898	50504	49943
85	39329	36492	31309

IES INDOOR REPORT
PHOTOMETRIC FILENAME : L041609102.IES

CANDELA TABULATION

	<u>0.0</u>	<u>22.5</u>	<u>45.0</u>	<u>67.5</u>	<u>90.0</u>
0	250.24	250.24	250.24	250.24	250.24
5	249.02	249.19	249.19	249.36	249.53
10	245.84	246.13	246.21	246.34	246.51
15	240.97	241.26	241.31	241.56	241.81
20	234.09	234.43	234.59	234.89	235.10
25	225.03	225.62	225.87	226.08	226.45
30	214.29	214.83	215.17	215.30	215.55
35	202.12	202.54	202.75	203.05	203.38
40	187.44	188.20	188.53	188.66	189.29
45	171.50	172.00	172.34	172.67	172.92
50	153.88	154.68	154.97	155.14	155.39
55	134.83	135.34	135.67	136.05	136.76
60	114.36	114.53	114.82	115.62	115.70
65	92.80	93.22	93.43	93.80	93.97
70	70.65	71.23	71.40	71.19	71.32
75	49.00	48.66	48.62	48.45	48.08
80	29.28	28.86	28.49	27.98	27.86
85	12.75	12.59	11.83	10.61	10.15
90	0.00	0.00	0.00	0.00	0.00

IES INDOOR REPORT
PHOTOMETRIC FILENAME : L041609102.IES

ZONAL LUMEN SUMMARY

Zone	Lumens	%Lamp	%Fixt
0-20	91.85	N.A.	12.50
0-30	195.94	N.A.	26.70
0-40	322.73	N.A.	43.90
0-60	576.77	N.A.	78.50
0-80	721.06	N.A.	98.10
0-90	735.13	N.A.	100.00
10-90	711.44	N.A.	96.80
20-40	230.89	N.A.	31.40
20-50	363.79	N.A.	49.50
40-70	346.40	N.A.	47.10
60-80	144.29	N.A.	19.60
70-80	51.92	N.A.	7.10
80-90	14.08	N.A.	1.90
90-110	0.00	N.A.	0.00
90-120	0.00	N.A.	0.00
90-130	0.00	N.A.	0.00
90-150	0.00	N.A.	0.00
90-180	0.00	N.A.	0.00
110-180	0.00	N.A.	0.00
0-180	735.13	N.A.	100.00

Total Luminaire Efficiency = N.A.%

ZONAL LUMEN SUMMARY

Zone	Lumens
0-10	23.70
10-20	68.15
20-30	104.09
30-40	126.80
40-50	132.90
50-60	121.13
60-70	92.37
70-80	51.92
80-90	14.08
90-100	0.00
100-110	0.00
110-120	0.00
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00


IES INDOOR REPORT
PHOTOMETRIC FILENAME : L041609102.IES

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	109	104	99	96	106	102	98	94	97	94	91	93	91	88	90	88	86	83
2	99	90	83	78	96	88	82	77	85	79	75	82	77	73	78	75	71	69
3	90	79	71	64	87	78	70	64	75	68	63	72	66	61	69	64	60	58
4	82	70	61	54	80	69	60	54	66	59	53	64	57	52	62	56	52	49
5	75	62	53	47	73	61	53	46	59	52	46	57	51	45	55	49	45	43
6	70	56	47	41	68	55	47	40	53	46	40	52	45	40	50	44	39	37
7	65	51	42	36	63	50	42	36	48	41	35	47	40	35	46	40	35	33
8	60	46	38	32	58	46	37	32	44	37	32	43	36	31	42	36	31	29
9	56	43	34	29	55	42	34	29	41	33	28	40	33	28	39	33	28	26
10	53	39	31	26	51	39	31	26	38	31	26	37	30	26	36	30	25	24

POLAR GRAPH



Maximum Candela = 250.24 Located At Horizontal Angle = 0, Vertical Angle = 0
1 - Vertical Plane Through Horizontal Angles (0 - 180) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (0) (Through Max. Cd.)