

GM Lighting

LEDTASK™ 24VDC SUPER HIGH OUTPUT FLEXIBLE LED LINEAR RIBBON

Project: _____

Type: _____

Location: _____

Contact Phone: _____

PRODUCT DESCRIPTION

A 24VDC 'Super High Output' flexible LED linear ribbon that conforms to straight, curved and irregular architectural coves, bannisters, recesses and other constructs where even, energy saving hi-power LED illumination is specified. Available in a 5 meter (16.4') reel. Ribbon can be cut in field to achieve desired length.

PRODUCT SPECIFICATIONS

Construction: LEDTask 24VDC Super High Output Flexible LED Ribbon incorporates 1200 LED diodes per reel and are mounted to a flexible adhesive backed buss. The ribbon is conveniently wound on a 5 meter (16.4 ft) reel. Each reel is shipped in a moisture proof package and is also supplied with appropriate connectors.

Connectors: Five meter reel includes 3 - DTW-24 ribbon to power supply connectors, with 24" of lead affixed to start of reel. One meter reel includes (1) DTW-24 affixed to the start of the reel and (1) DTC-1

Electrical: Each LED is .08W. 5.85W per foot. 5 meter reel is 4.5 amps and 96 watts. **50,000 hour LED life.**

Color Temperature: 2700K, 3000k, 3500K and 4200K
Power Supplies: See chart at right

Dimming: Yes with dimmable power supplies (see at right) utilizing low voltage magnetic on/off wall dimmer (GMWD-600).

Cutting and Mounting: Linear ribbon can be cut every 6 pairs of LED diodes. Ribbon utilizes 3M double stick tape.

Label: ETL



Warranty: 5 year warranty

LED LINEAR RIBBON CONNECTORS and ACCESSORIES

Cat. No.	Description
DTC-1	Ribbon to ribbon connector
DTC-3	3" flexible ribbon to ribbon connector
DTC-12	12" flexible ribbon to ribbon connector
DTC-24	24" flexible ribbon to ribbon connector
DTC-48	48" flexible ribbon to ribbon connector
DTC-60	60" flexible ribbon to ribbon connector
DTW-6	6" flexible ribbon to power supply connector
DTW-24	24" flexible ribbon to power supply connector
DTW-60	60" flexible ribbon to power supply connector

Cat. Number	Length	Total LED's	LED Wattage	Amps per reel	Lumens per ft	Color	LED Life
LTR24024-HO-27	1M (39")	240	.08W (5.85W/ft)	0.6	314	2700K Warm White	50,000 hrs
LTR24024-HO-30	1M (39")	240	.08W (5.85W/ft)	0.6	350	3000K Warm White	50,000 hrs
LTR24024-HO-35	1M (39")	240	.08W (5.85W/ft)	0.6	379	3500K Warm White	50,000 hrs
LTR24024-HO-42	1M (39")	240	.08W (5.85W/ft)	0.6	427	4200k Cool White	50,000 hrs
LTR120024-HO-27	5M (16.4')	1200	.08W (5.85W/ft.)	4.0	314	2700K Warm white	50,000 hrs.
LTR120024-HO-30	5M (16.4')	1200	.08W (5.85W/ft.)	4.0	350	3000K Warm white	50,000 hrs.
LTR120024-HO-35	5M (16.4')	1200	.08W (5.85W/ft.)	4.0	379	3500K Warm White	50,000 hrs
LTR120024-HO-42	5M (16.4')	1200	.08W (5.85W/ft.)	4.0	427	4200K Cool White	50,000 hrs

* Includes 24" of lead on the ribbon and (3) DTW-24 24" flexible ribbon to power supply connectors. **Kelvin temperature (color) ±200.



24VDC ELECTRONIC POWER SUPPLIES DIMMABLE MAGNETIC POWER SUPPLIES



Cat. No.	Description
LTP-24-48	48W - 2 Amps - 120V Cord and Plug (126"). Short circuit, overload protection - LED indicator for power on.
LTP24-90	90W - 3.75 Amps - 120V Cord and Plug (72"). Short circuit, overload protection . LED indicator for power on.
LTH24-4	100W - 4.2 Amps - 120V - Universal AC input - Short circuit overload protection. LED indicator for power on. Metal.
LTH24-8	200W - 8.4 Amps - 120V - Universal AC input - Short circuit overload protection. LED indicator for power on. Metal.
LTH-60-DIM	Dimmable 60W - 2.5 Amps - 120V, 240V or 277V - Universal AC input 120V, 240V or 277V - 50 or 60 Hz. - no external fusing.
LTHM100-DIM-24	Dimmable 100W - 4 Amps - 120V / 60 Hz - Double section bobbin - ETL for indoor and outdoor use. Manual reset.
LTHM200-DIM-24	Dimmable 200W - 8 Amps - 120V / 60 Hz - Double section bobbin - ETL for indoor and outdoor use. Manual reset.
LTHM300-DIM-24	Dimmable 300W - 12 Amps - 120V / 60 Hz - Double section bobbin - ETL for indoor and outdoor use. Manual reset
GMWD-600	600W magnetic wall dimmer with on/off switch. Single pole. 120V/60Hz. White finish. For use with all GM Lighting 12VDC and 24VDC Mag. Dimmable Power Supplies

For power supply dimensions, please see www.gmlighting.net



GM Lighting, LLC • 9830 W. 190th St. • Unit F • Mokena, IL 60448
Toll-Free: (866) 671-0811 FAX: (708) 478-2640 • www.gmlighting.net
e-mail: sales@gmlighting.com • Specifications subject to change without notice.



LTR120024-HO_081915