

MicroTask

120V Mini IC Rated Round Adjustable Gimbal LED Downlight

GM Lighting®

Project Name

Type

Catalog #

Date

PRODUCT OVERVIEW

Excellent color rendition and high lumens in a 3" mini-adjustable, IC rated, damp location, round trim downlight that features an inline junction box connected by a modular twist-connector. 360° rotation, 30° tilt on axis for precise beam control. Perfect for wall wash or focus aiming applications. Available in 2700K or 3000K color temp and white semi-gloss finish. Flexible modular extended connectors available. Extenders available. See below.



FEATURES

- 3-3/8" trim diameter, 1-1/2" recess depth
- Dimmable
- Up to 550 lumens
- 90+ CRI
- IC rated (ceiling clearance required: 1-1/2" for Romex, 3-1/2" for MC or BX installations)
- Adjustable gimbal (360° rotation - 30° tilt on axis)
- Die-cast construction
- Quick and easy installation
- In-line junction box connected by 12" TwistLock cable
- Snap-in spring clips installation
- Shallow mount

SPECIFICATIONS

ELECTRICAL

- 120V
- 8W

LABEL

- ETL
- Title 24

OPTICS

- 2700K, 3000K
- 30° beam angle

WARRANTY

- 5 years



ORDERING INFORMATION

Example: MDL-3AR-30-WH

Model	-	Color Temp.	Finish
MDL-3AR		27 (2700K)	WH (WHITE)
		30 (3000K)	

CONNECTORS AND ACCESSORIES

Catalog No.	Description
MDL-5FT-EXT	5' EXTENSION CORD FOR MDL SERIES DOWNLIGHTS
MDL-10FT-EXT	10' EXTENSION CORD FOR MDL SERIES DOWNLIGHTS
MDL-20FT-EXT	20' EXTENSION CORD FOR MDL SERIES DOWNLIGHTS
UNV-NCP	NEW CONSTRUCTION PLATE FOR ALL RSD SERIES DOWNLIGHTS

LUMEN TABLE

Catalog No.	Recess Depth	Trim Diameter	Wattage	Lumens	CRI	Color Temp.
MDL-3AR-27-WH	1-1/2"	3-3/8"	8W	545	90+	2700K
MDL-3AR-30-WH				550		3000K

DIMENSIONS

