

120V LED 5CCT Selectable White Undercabinet Light Bar

PRODUCT OVERVIEW

Able to achieve color temps. of 2700K, 3000K, 3500K, 4000K and 5000K in a single fixture, this dimmable, adjustable Kelvin undercabinet fixture features excellent color rendering in a powder coated aluminum housing with polycarbonate lens. Low profile and easy to mount in 8", 16", 24" and 32" lengths.

FEATURES

- Under 1" mounting depth
- Screw slots for easy wiring access
- Rated at 6W (8"), 10W (16"), 14W (24") and 16W (32")
- Selectable: 2700K / 3000K / 3500K / 4000K / 5000K
- Supplied with Wago® Connectors for easy connection
- Includes captive mounting screws
- Powder coat aluminum housing
- Dimmable (Triac)
- Units join securely together with connectors
- Available in 8", 16", 24" and 32" lengths
- Dry / Damp indoor location

SPECIFICATIONS

ELECTRICAL

- 120V (remote power supply not required)
- Color temps accessed through temperature slide switch

OPTICS

- 90+ CRI
- 2700K / 3000K / 3500K / 4000K / 5000K

CERTIFICATIONS

- ETL listed
- Title 24

WARRANTY

- 5 years

Project Name	Type
Catalog #	Date



ORDERING INFORMATION

Example: UCTUN-8-WH

Model	Length	Finish
UCTUN	8" / 203mm (8)	White (WH)
	16" / 406mm (16)	
	24" / 610mm (24)	Bronze (BZ)
	32" / 1100mm (32)	

NOTE: Each fixture includes (1) UCTUN-EZ-1 connector and (1) conduit fitting and captive mounting screws.

Catalog No.		2700K	3000K	3500K	4000K	5000K
UCTUN-8-WH UCTUN-8-BZ	Lumens	380	390	405	420	430
	Lumen Factor	0.97	1.00	1.04	1.08	1.10
UCTUN-16-WH UCTUN-16-BZ	Lumens	610	630	670	690	690
	Lumen Factor	0.97	1.00	1.06	1.10	1.10
UCTUN-24-WH UCTUN-24-BZ	Lumens	970	995	1065	1125	1095
	Lumen Factor	0.97	1.00	1.07	1.13	1.10
UCTUN-32-WH UCTUN-32-BZ	Lumens	1090	1035	1150	1220	1190
	Lumen Factor	1.05	1.00	1.11	1.18	1.15

NOTE: When using 3000K ies files, use Lumen Factor to get Lumen values for other Color Temperatures (CCT). Example: UCTUN-24-WH, 995lm x 1.13 = 1124lm at 4000K

ACCESSORIES

Catalog No.	Description
UCTUN-CP6-WH	Plug-in 6' power cord - black
UCTUN-EZ-1-WH	Fixture to fixture connector - white
UCTUN-EZ-1-B	Fixture to fixture connector - black
UCTUN-EZ-6-WH	6" flexible fixture to fixture connector - white
UCTUN-EZ-6-B	6" flexible fixture to fixture connector - black
UCTUN-EZ-12-WH	12" flexible fixture to fixture connector - white
UCTUN-EZ-12-B	12" flexible fixture to fixture connector - black
UCTUN-QB-WH	Quick-box wiring junction box with EZ connectors and knock-outs

DIMENSIONS

