

# Multi-Color and White Curvable Sideflex LED Tape

GM Lighting's narrow profile LED with curvable Side-Flex features a revolutionary solution for bendable and dynamic lighting applications. Its horizontal bend feature allows for incredible flexibility, making it perfect for intricate designs and unique lighting setups. With the addition of 2700K, 3000K and 4000K White LEDs, an amazing combination of color and general lighting is enabled. The well-diffused light ensures an even, soft, and eye-friendly illumination, creating a pleasant ambiance in any space.

- Simple field assembly, factory custom cuts available
- 2W/ft, 24Vdc
- 4mm slim dimension LED neon light
- Red, Orange, Amber, Green and Blue colors for vibrant applications
- White LEDs for general and task lighting (2700K/3000K/4000K)
- Cuttable Increment: 1"
- 30mm bending diameter for tight curves and flowing shapes
- IP65 rated for outdoor, wet location
- Working Temp = -4°F to +104°F (-20°C to +40°C)









# Multi-Color and White Curvable Sideflex LED Tape

## **RECOMMENDED CONTROLLERS & DRIVERS**

LUXcontrol Smart 2.4 GHz WiFi Controller, Standard 12V/24V Low Voltage, SHWC (use with 24V LD-E non-dimming power supply)



LineDrive Electronic Multi-Dimmable Power Supply For Direct Wiring To Dimmers LD-XD-UNV - Series (24V)



## **ORDERING INFORMATION**

Example: NVM24S-2W-27K-16

Catalog No.	Watts/Ft Max.	Color Temp	Lumens/Ft	Max. Run
NVM24S-2W-27K-16	2W	2700K	70 Lm	16 ft 4 in
NVM24S-2W-30K-16	2W	3000K	68 Lm	16 ft 4 in
NVM24S-2W-40K-16	2W	4000K	59 Lm	16 ft 4 in
NVM24S-2W-AM-16	2W	Amber (590nm pk)	14 lm	16 ft 4 in
NVM24S-2W-BL-16	2W	Blue (470nm pk)	13 lm	16 ft 4 in
NVM24S-2W-GR-16	2W	Green (519nm pk)	59 lm	16 ft 4 in
NVM24S-2W-OR-16	2W	Orange (610nm pk)	15 lm	16 ft 4 in
NVM24S-2W-RD-16	2W	Red (630nm pk)	7 lm	16 ft 4 in

### ACCESSORIES

Catalog No.	Description		
NVM24S-EC	End Cap, Molded Silicone (sealant not included)		
NVM24S-MC-A	Back Mounting Clips, Aluminum (20 clips, 20 SS screws)		
NVM24S-CHL-A4	Rigid Channel, Aluminum, 4ft		
NVM24S-FLEX-CHL	Flexible Channel, Stainless Steel, 1m 105 holes & screws		
TAPE-DS-VHB-4MMW	4mm wide x 6m VHB tape		
TOOL-PH0-HEX	PH0 Philips head, 1/4" hex drive bit		



©2024 GM LIGHTING, LLC • www.gmlighting.net • Specifications subject to change without notice 18700 Ridgeland Ave., Tinley Park, IL 60477 • Toll-Free: (866) 671-0811 FAX: (708) 478-2640 • tech@gmlighting.net